

JW Plus Series

n-Type Bifacial Single Glass Mono Module

JW-HT132N-R2 595-625W

Maximum
Power Output

625W

Maximum Module
Efficiency

23.1%

Power Output
Tolerance

0~+3%

n-TOPCon



Higher Customer Value

- Lower 1st-year and annual degradation
- Lower system BOS cost, higher power generation, lower LCOE, and higher ROI



Higher Power Generation Gain

- Excellent IAM property and better weak illumination response
- Lower 1st-year degradation (1%) and annual degradation (0.4%)
- Lower temperature coefficient (-0.28%) and lower operating temperature, resulting in more power generation
- The application of transparent grid backsheets with high light transmittance and self-cleaning properties, enhancing power generation gain




High Reliability

- Apply latest generation TOPCon technology with lower LID and LETID
- Apply innovative non-destructive cutting technology to reduce the risk of micro cracks
- Fully tempered glass with higher strength and superior hail resistance
- Withstand harsh environmental conditions, such as salt mist, ammonia, PID, dust and sand, and high-temperature and high-humidity



High Safety

- Latest TOPCon technology with no polysilicon wrap around, zero leakage current and better resistance to hot-spot
- Pass mechanical load test of 5400Pa on the front side and 2400Pa on the back side




Munich RE   



IEC 61215(2021)/IEC 61730(2023)/IEC 61701/IEC 62716
ISO 9001:2015: Quality Management System
ISO 14001:2015: Environment Management System
ISO 45001:2018: Occupational health and safety
IEC 62941:2019: Quality system for PV module manufacturing

Linear Performance Warranty



12 Years Product Material & Workmanship 30 Years Linear Performance Warranty

Version 2024.12 ©Jolywood (Taizhou) Solar Technology Co., Ltd. All rights reserved.

www.jolywood.cn

Add: No.6 Kaiyang Rd., Jiangyan Economic Development Zone,
Taizhou, Jiangsu Province, China, 225500

TEL: +86 523 80612799

Email: info@jolywood.cn



JW-HT132N | n-type Bifacial Single-Glass Mono Module

Electrical Properties | STC*

Testing Condition	Front Side	Front Side	Front Side	Front Side	Front Side	Front Side	Front Side
Peak Power (P _{max}) (W)	595	600	605	610	615	620	625
MPP Voltage (V _{mp}) (V)	40.20	40.38	40.56	40.74	40.92	41.10	41.28
MPP Current (I _{mp}) (A)	14.80	14.86	14.91	14.97	15.03	15.08	15.14
Open Circuit Voltage (V _{oc}) (V)	46.89	47.09	47.29	47.49	47.69	47.89	48.09
Short Circuit Current (I _{sc}) (A)	15.67	15.72	15.77	15.82	15.87	15.92	15.97
Module Efficiency (%)	22.0	22.2	22.4	22.6	22.8	23.0	23.1

*STC: Irradiance 1000 W/m², Cell Temperature 25°C, AM1.5

The data above is for reference only and the actual data is in accordance with the practical testing
Power Measurement Tolerance ±3%

Electrical Properties | NMOT*

Testing Condition	Front Side	Front Side	Front Side	Front Side	Front Side	Front Side	Front Side
Peak Power (P _{max}) (W)	446	449	453	457	461	464	468
MPP Voltage (V _{mp}) (V)	38.49	38.67	38.84	39.01	39.18	39.36	39.53
MPP Current (I _{mp}) (A)	11.58	11.62	11.67	11.71	11.76	11.80	11.84
Open Circuit Voltage (V _{oc}) (V)	44.89	45.08	45.28	45.47	45.66	45.85	46.04
Short Circuit Current (I _{sc}) (A)	12.66	12.70	12.74	12.78	12.82	12.86	12.90

*NMOT: Irradiance 800 W/m², Ambient Temperature 20°C, Wind Speed 1 m/s

Electrical Properties Under Different Rear Gain | JW-HT132N-R2-610

Power Gain (%)	Peak Power (P _{max}) (W)	MPP Voltage (V _{mp}) (V)	MPP Current (I _{mp}) (A)	Open Circuit Voltage (V _{oc}) (V)	Short Circuit Current (I _{sc}) (A)
10	671.0	40.74	16.47	47.49	17.41
15	701.5	40.74	17.22	47.49	18.20
20	732.0	40.84	17.92	47.59	18.95
25	762.5	40.84	18.67	47.59	19.74
30	793.0	40.84	19.42	47.59	20.53

Operating Properties

Operating Temperature	-40°C~+85°C
Maximum System Voltage	1500V (IEC)
Maximum Series Fuse Rating	35A
Bifaciality*	80%
Static Load	Front side 5400Pa, Rear side 2400Pa

*Bifaciality=P_{max}rear (STC) /P_{max}front (STC) , Bifaciality tolerance:±5%

Temperature Coefficient


Temperature Coefficient of P _{max}	-0.280%/°C
Temperature Coefficient of V _{oc}	-0.250%/°C
Temperature Coefficient of I _{sc}	+0.045%/°C
Nominal Operating Cell Temperature	45±2°C

Specification


Number of Cells	132pcs
Module Dimension	2382mm*1134mm*30mm
Weight	28.7kg
Front Glass	3.2mm Tempered glass
Frame	Anodized Aluminium Alloy
Junction Box	IP68 (3 diodes)
Length of Cable	4.0mm ² , +300mm/-180mm (Cable length can be customized)
Packaging Configuration	36pcs/Pallet, 720pcs/40HQ Container

*The specification and key features described in this datasheet may deviate slightly and are not guaranteed. Due to ongoing innovation, R&D enhancement, Jolywood (Taizhou) Solar Technology Co., Ltd. reserves the right to make any adjustment to the information described herein at any time without notice. Please always obtain the most recent version of the datasheet which shall be duly incorporated into the binding contract made by the parties governing all transactions related to the purchase and sale of the products described herein.


Engineering Drawing (unit: mm)



Characteristic Curves | JW-HT132N-R2-610



I-V Characteristics At Different Irradiations



P-V Characteristics At Different Irradiations

www.jolywood.cn



Add: No.6 Kaiyang Rd., Jiangyan Economic Development Zone,
Taizhou, Jiangsu Province, China, 225500

TEL: +86 523 80612799

Email: info@jolywood.cn

